

## Pick and Place Quad Copter Drone

D.Pallavi<sup>1</sup>, A.Sneha Latha<sup>2</sup>

<sup>1,2</sup>(Department of ECE, HITAM college of Engineering and Technology, Hyderabad)

Corresponding Author: saipallavijoshi789@gmail.com

### To Cite this Article

Pallavi and Sneha Latha, "Pick and Place Quad Copter Drone", *Journal of Engineering Technology and Sciences*, Vol. 01, Issue 03, November 2024, pp.:17-21

---

**Abstract:** In particular, a quad can vertically fly stably, and it can be used in a region such as when loading a mass. Low power microcontrollers are now affordable and efficient, and with technological advances public much more encouraged to build their own quadcopters. This project aims to improve efficiency of existing auto commands such as auto landing using an existing quadcopter package built, modified & developed to collect, store and collect GPS data during flight. Project used the aero quad Quadcopter Package. There were the bases, the engines, the electrical speed controls, the Arduino Super production panels and sensor boards in this kit. This box included batteries, transmitter, receiver, GPS module and a micro-SD card adapter. The aero quad software has been modified so that the modules connect to the quadcopter kit correctly. Specific components have been very carefully examined and verified. To adequately stabilize the axis, a butterfly—as they are affectionately called—was fitted for PID test benches, which were then modified and calibrated in order to change the PID controller operation. This allows it to now stay stable, calculate its location if GPS is available, record and store data. A safe nimble quadcopter was produced during this phase and the most for the majority of the objectives were met.

**Keywords:** Quad copter, flight controller, Brushless engine, Propellers, Lithium Polymer Battery, RC Sender & Receiver.

---

### I. Introduction

A quadcopter is a helicopter with four rotors called quadrotor. Quadrotor helicopters and convertiplanes have been flown but the arrangement was a mystery until the modern UAV (or drone) came along. The small quadrotors' small size and low inertia allow a very simple flight control system, greatly increasing their usefulness in this application. Each rotor actually produces lift and torque around the rotation center of the rotor, as the rotor passes through center of rotation, and drag opposed to the vehicle orientation, as the rotor moves. Usually, most Quadcopters have two (CW) and two (CCW) rotors (CCW). The lift and torque are produced by varying each rotor independently, and speed is varied to produce flight control. The net centre of thrust controls pitch and roll and the net torque controls yaw[3]. Like a traditional helicopter, a quadcopter does not have the cyclic pitch control to change the angle of the blades moving around the rotor hub, but it is the angle the blades can be pitched to change that changes. And they solved at least some of the problems that beset vertical flight. Early flying made quadcopters (known previously as 'quadrotors' or just 'helicopters') look like something that could... Shorter blades are easier to build and may eliminate torque induced control problems (particularly for problems of efficiency that are attendant to the tail rotor which is an inefficient propulsion system). Among the numerous designed of the manned designs were developed in the years of 1920s and 1930s. [4] The first were these aircraft, which were the first ever heavier than air vertical take off and landing (VTOL) aircraft. However, early prototypes were not very good and in later versions too much of the pilot's work load was created by inadequate stability augmentation, and a lack of control authority[5].

### II. Survey on Literature


Works using FC and development on Arduino are presented in the publications. can be an Arduino's brains on a DIY FC or an add on a (already built) FC. The telemetry's that is dealing with there time and the allocators are FC's, and the Stabilizers learn the roles so that they know what he said. Evaluations of these results indicate that the use of Arduino in building FC as an integrated component improves control via both the stabilization and control tasks since the control decisions are retrieved from balancing sensor, namely gyro- and/or accelerometer, which is performed by Arduino. It is possible that a given Arduino cannot be utilized as a FC, and simultaneously serves as a

conduit through which contact information is passed from a telemetry module located on the track. If the Arduino is used to carry this responsibility on the existing FC, then the FC itself automatically provides all stabilizing features, based on the FC's performance characteristics. In fact, when we connect it with a sensor, we can actually turn its data into meaningful information and use it to analyze sensor data from a telemetry module, or whatever the consumer is going to use the Quadcopter.

### III. System Proposed

The purpose of this project is to adapt already working Quadcopter package to stabilize flying and auto landing and to collect GPS data and store. Chassis, engines, electrical speed controls, Arduino Super creating panel and sensor boards and the Aeroquad software were used on the project. It came with a Aeroquad quadcopter kit. Inside the box are batteries, transmitter, receiver, a GPS module and a micro SD card adapter. The aeroquad software has been modified though to connect to the quadcopter kit. It's been carefully inspected and verified (certain parts here). Bespoke PID test benches were used to bring the PID controller into stability on the - axis. The quadcopter can now stabilize, having it's GPS position, and can also save and record data. Most of the objectives that were produced a safe and nimble quadcopter were fulfilled in this phase.

**Block Diagram:**



**Figure no 1:** Block diagram

### IV. Hardware Components

**Flight Microcontroller:** KK1 is a prequel of KK2. The KK2.0 Multi Rotor Controller is a multi rotos aircraft flight board (Tricopters, Quadcopters, Hexcopters etc). I want to take off smoothly. Each of the 3 on board gyros (roll, pitch, and yaw) generate a signal that is sent to the Atmega324PA IC. Vehicle speed is taken under control by using the Electronic Speed Controller (ESC). The speed control of an electric motor is provided by an electronic speed control, also known as an ESC. Additionally, it can reverse the engine for use with dynamic braking, or this. Radio controlled models are powered by electric and these miniature electronic speed controllers are used.

**Battery made of Lithium Polymer:** For all those of you who're into the electric RC and quadcopter world, there's been one type of rechargeable battery on the block that has swept over the electric RC and especially the quadcopter market based on beads: Li Polymer (LIPO) batteries. Here are the main reasons why it is viable for any of your fuel powered vehicle to become electric flying and this and the reasons why it is true.

**Frame for a QUAD Copter:** It all comprises the framework. Increasingly one of the most vital factors in the construction of the quadcopter is construction of the overall building and inhibiting the vibration of the motors and other electronics. Which means we've already got a process in play of course and that means you have to be extremely precise in development. This means they've got to be both heavy and light.

**Propellers:** You were just to encourage your quadcopter's propellers to push as propulsion and torque in order to move your quadcopter and navigate. The weights or grams are usually the amount of pounds of upward thrust. There was a mistake. As with all flight Lilium's quadcopter is faster if the propellers spin faster.

**DC Motor without Brushless:** An internal commutation brushless DC motor is used for the intended direct power supply. The first commercial application of electric control for mechanical resources was with DC delivery systems for motors in commercial and industrial structures for over a century with brushed motors. Brushed DC engines can be run at varying speeds (depending on operating voltage, or magnetic field power).

**Transmitter (RC):** If you have an RC toy, you've got a small portable device sporting maybe a few controls and a radio transmitter. With a frequency, the transmitter sends a signal out to the toy's receiver. It is a signaling management and transmitting device with 9 volt battery which provides a power source to its signal management and transmitting.

**Receiver:** The RC Toy is divided into particular sections. The remote control provides a wireless transmitter, which transmits at a given frequency, to acquire the receiver. Receiver: The signal the transmitter sends tells the receiver it is always installed and always on.




Figure no 2: Flow chart

**Algorithm:**


1. Write sensor config and activate generator
2. Under the control of engines via RX.
3. Steering control is used to switch engines off.
4. keep the drone engine howler safe
5. Benefits from Pause STOP:
  - Quickly monitor and steer multi rotors drones.
  - They could float too.
  - They will be able to fly and land on their feet.

**Context:**

- One of the big things that makes a cruising robot different is that it's got legs.
- Extremely secure
- Will seek lost children, and seek offenders.

## V. Result

With the pick and position mechanism developed, the quad copter drone has been successfully deployed.





## **VI. Conclusion**

From the preceding subject of course, it may be deduced that this, like other people that have built technology, has both great benefits and disasters.

## **VII. Future Perspectives**

We will provide an FC that is qualified to fly autonomously as a possible advance or something researchers working on autonomous navigation for robots may find interesting. The Pixhawk 3DR, of course, is a fantastically suitable flight computer for this sort of project, given its purpose-built independent flight design, its open source firmware and software so you can edit to get something that works, and there are many (free) GCS software web apps running on it.

## **References**

- [1]. Anata Rao, Krishna Rao and Mohan Krishna, IEEE Conference Proceedings, Delhi, Smart Technologies in Communication Systems, pp:23-32, Vol (5), Issue (2), 2021
- [2]. Chung Lee: How to control Quad copter in communication systems", (2020), Science Direct vol(4), Issue (1)
- [3]. E. Swathi Priya, M. Manoj Kumar Yadav, M. Swapna Dutt, M. P. Prasad , "SPWM based Battery Module Integrated Stand Alone Single Capacitor Inverter for Rural Development", Journal of National Critical Reviews, Vol 9, Issue 2, pp. 203-212, August 2021
- [4]. Kadamatti Vihari, M.: Operation Quad Copteran on flight for Drone (2020), Elsevier Proceedings
- [5]. Md Abdul Khan Ahad, Ch Lakshmi Priya, K Amrutha Rao, M P Prasad Singh Rao, K Rajasekhar Reddy, "Fuzzy and Neural Based Modeling & Analysis for short-distance DC Power Transmission Line.", Jour. of Adv. Research in Statical and Dynamical & Control Systems, Vol. 2, Iss. 4, pp. 1231-1242, May 2018.
- [6]. Beginners guide Quadcopter drone, Drone Trest (2012), conference proceedings IEEE Bombay, vol(5), Issue (1) pp34-39, 2012
- [7]. Appa Rao, Krishna Rao and Niharika, conference proceedings, "Implementation of Drone in scientific field in various scenarios", DRDO, vol (4), Issue (2), 2010
- [8]. Carry on Drone Technologies in Canada, "Implementation of Quadcopter in research in scientific field", Springer, vol (3), Issue (2), pp:12-21, 2021